

## Fork Slot Truss Jib

Fork Slot Truss Jibs - Jib attachments are made to be able to be used on extendable-reach lifts, rough terrain straight-mast lift trucks and also on industrial lift trucks. Forklift jib cranes install onto the forklift by means of inserting both forks into the fork pockets. The rear of the jib crane then seats against the rear of the fork and a safety chain wraps the forklift carriage to hold it into place.

### Jib Boom Forklift Attachment Load Capacity

The most load capacity intended for forklift jibs in both the retracted or extended positions range from 1935 lbs up to 6000 pounds. It is a good idea to ask a material handling specialist regarding the restrictions for your particular use. The load capacity ratings are used for the jib itself and not the lift truck or the utmost load that could be handled safely making use of a particular lift truck. It is essential to keep in mind that at any time when whichever accessories like for example a lift truck jib are connected to the lift truck, the new center of gravity made by the accessory would lessen the general lift capacity of the forklift. There are instructions accessible that offer details on the way to correctly estimate these load limits.

Prior to using whatever lift truck jib, be sure that the hooks and shackles are properly secured to the forklift. Be sure and also double check that the pins are tight. It is very important that the weight calculations have been correctly made and double checked. Bear in mind to take into consideration the fact that rated capacities occasionally lessen every time the boom is in a raised position, every time the boom is extended with telehandlers or even every time the mast is slanted forward.